

Product Specification

Item # SC65R400600

Description VACUUM POUCH 400 X 600 RECYCLABLE 500 PER BOX

 Unit
 1000

 Pallet Qty
 20

Product Category 41124 Recyclable Vacuum Pouches

Unit Weight 15

Specification Details

Structure: PA/PE Multilayer Co-extruded barrier film **Excellent:** Seal ability & Mechanical strength

Property	Method	Value
AVG. THICKNESS 2σ (+/- 10 %)		65 micron
DART IMPACT (Gm. at 66 cm)	ASTM D1709-	-03 >400
TENSIL STRENGTH (N/15 mm)		
MD	ASTM D-882	>30
TD	ASTM D-882	>30
ELONGATION (%)		
MD	ASTM D-882	>400
TD	ASTM D-882	>400
C.O.F. (F□F)		
INNER	ASTM D-1894	< 0.3
OTR 23 °C/ 0 % Rh (cc/m²/day)	ASTM D3985-	-05 ≤69
WVTR 38 °C & 90 % RH (gm/m ² /da	y) ASTM F 1249	-06≤7

Storage recommendations: Store in a clean, cool & dry place 15-35°C, 30-80% RH, for up to 12 months.

Do not store in daylight or outside. Protect from rain & direct sunlight.

Avoid direct contact to floor and walls. Keep in original packaging and remove all the protective packaging material before using the products.

Food Compliance: The films are made of raw materials (inputs) such as polymers used in the above products suitable for food contact in according to FDA and/or EC regulations.

MSDS

Films & pouches are recyclable and do not cause harm to the environment. They contain no CFC's or heavy metals such as Pb, Ba, Cd, Ag, Se.

Storage	Products should be stored in a clean cool dry place, not in direct sunlight, and at room temperatures not exceeding 25 degrees C.
Health Hazard	The products ought to be covered to prevent any risk of contamination
Fire Hazard	This product may burn. Fires are readily extinguished with water or foam.
Disposal	In accordance with the control of pollution act 1974.

Customer Approval of Specification		
	return this specification to technical@scobie-junor.co.uk to confirm formal acceptance of this specification. All ued will be deemed to be accepted if no communication to the contrary is received after 10 working days.	
Signature		
Print Name		
Position		
Dato		

While we have taken all reasonable steps to verify the accuracy of the information contained in this specification, no warranties are given to this effect and purchasers should determine for themselves whether products are suitable for their own specific use. The information contained in this specification is intended for the customer it has been issued to. It must not be reproduced, or the information contained therein passed on to any third party without the written consent of Scobie & Junor.

Issued electronically by Scobie & Junor (Estd. 1919) Ltd

Certified accurate on 20/05/2024



© 2024 Scobie & Junor (Estd. 1919) Ltd Group Headquarters 1 Singer Road, East Kilbride, Scotland, G75 0XS Tel: 01355 237041 Fax: 01355 576343 www.scobiesdirect.com Registered Scotland # 10710 VAT # GB 659 1432 23

Naas Branch Unit A3, M7 Business Park Naas, Co Kildare, Ireland Tel: 045 856 747 Fax: 045 856 726 Freephone: 1800 30 1919 VAT # IE 6540968 P