

Product Specification



Item # VI90200200
Description VACUUM POUCH 200 X 200 90MU 1000 PER BOX
Unit 1000
Pallet Qty 125

90 mic Barrier Film
7 layer PA/PA/PE BLOWN FILM
Excellent Sealability
Excellent Mechanical properties

SR.NO	Property	Value
1	AVG. THICKNESS (Mic)	90 (3.6 Mil)
2	DART IMPACT (gm at 66 cm)	800
3	TENSILE (N/15mm) MD TD	47 34
4	ELONG (%) MD TD	621 497
5	C.O.F. (F → F) OUTER INNER	0.414 0.231
6	SEAL STRENGTH (N/15mm)	24.74
7	OTR (23 deg c) DRY (cc/m2/day)	40
8	WVTR (90 % RH ,38 deg c)	3.5

Film complies with FDA, EC relevant regulations -food grade film.

This is to certify that the raw material (inputs) such as polymers, pigments, used in the above products are of virgin and food grade quality and also acceptable for incidental food contact and does not contain any substance which is listed in the negative lists. It also conforms to the positive list of constituents as prescribed the inputs incorporated in it also comply with FDA: CFR, title 21,177.1520 olefin polymer & EC 2002/72/EC,as amended up to EC directive 2005/79/EC – food grade

Typical values not specified limits.

Films & pouches are recyclable and do not cause harm to the environment. They contain no CFC's or heavy metals such as Sb, Cr, As, Pb, Ba, Cd, Ag or Se

Storage Products should be stored in a clean cool dry place, not in direct sunlight, and at room temperatures not exceeding 25 degrees C.

Health Hazard The products ought to be covered to prevent any risk of contamination

Fire Hazard This product may burn. Fires are readily extinguished with water or foam.

Disposal In accordance with the control of pollution act 1974.

© 2010, Scobie & Junor (Estd. 1919) Ltd, 1 Singer Road, East Kilbride, Scotland, G75 0XS
Tel: 01355 237041 Fax: 01355 576343 e-mail: info@scobie-junor.com
www.scobie-junor.com