

# **Product Specification**

| SC65R200300                                    |
|--|
| VACUUM POUCH 200 X 300 RECYCLABLE 1000 PER BOX |
| 1000   |
| 75   |
| 41124 Recyclable Vacuum Pouches                |
| 5  |
|  |

### **Specification Details**

**Structure:** PA/PE Multilayer Co-extruded barrier film **Excellent:** Seal ability & Mechanical strength

| Property                         | Method         | Value     |
|----------------------------------|----------------|-----------|
| AVG. THICKNESS 2Ïf (+/- 10 %)    | Â              | 65 micron |
| DART IMPACT (Gm. at 66 cm)       | ASTM D1709-03  | >400      |
| TENSIL STRENGTH (N/15 mm)        |                |           |
| MD                               | ASTM D-882     | >30       |
| TD                               | ASTM D-882     | >30       |
| ELONGATION (%)                   |                |           |
| MD                               | ASTM D-882     | >400      |
| TD                               | ASTM D-882     | >400      |
| C.O.F. (Fâ†′F)                   |                |           |
| INNER                            | ASTM D-1894    | < 0.3     |
| OTR 23 °C/ 0 % Rh (cc/m²/day)    | ASTM D3985-05  | ≤69       |
| WVTR 38 °C & 90 % RH (gm/m²/day) | ASTM F 1249-06 | ≤7        |

Storage recommendations: Store in a clean, cool & dry place 15-35ËšC, 30-80% RH, for up to 12 months.

Do not store in daylight or outside. Protect from rain & direct sunlight.

Avoid direct contact to floor and walls. Keep in original packaging and remove all the protective packaging material before using the products.

**Food Compliance:** The films are made of raw materials (inputs) such as polymers used in the above products suitable for food contact in according to FDA and/or EC regulations.

#### MSDS

Position

Films & pouches are recyclable and do not cause harm to the environment. They contain no CFCâ€<sup>™</sup>s or heavy metals such as Pb, Ba, Cd, Ag, Se.

| Storage       | Products should be stored in a clean cool dry place, not in direct sunlight, and at room temperatures not exceeding 25 degrees C. |  |
|---------------|---|--|
| Health Hazard | The products ought to be covered to prevent any risk of contamination   |  |
| Fire Hazard   | This product may burn. Fires are readily extinguished with water or foam.   |  |
| Disposal      | In accordance with the control of pollution act 1974.   |  |

#### **Customer Approval of Specification**

| Please sign and return this specification to <b>technical@scobie-junor.co.uk</b> to confirm formal acceptance of this specification. All specifications issued will be deemed to be accepted if no communication to the contrary is received after 10 working days. |  |            |  |  |  |  |
|---|--|------------|--|--|--|--|
| Signature   |  | Print Name |  |  |  |  |
|   |  |            |  |  |  |  |

Date

While we have taken all reasonable steps to verify the accuracy of the information contained in this specification, no warranties are given to this effect and purchasers should determine for themselves whether products are suitable for their own specific use. The information contained in this specification is intended for the customer it has been issued to. It must not be reproduced, or the information contained therein passed on to any third party without the written consent of

Scobie & Junor.

## Issued electronically by Scobie & Junor (Estd. 1919) Ltd Certified accurate on 27/08/2025



© 2025 Scobie & Junor (Estd. 1919) Ltd 1 Singer Road, East Kilbride, Scotland, G75 0XS Tel: 01355 237041 www.scobiesdirect.com Registered Scotland # 10710 VAT # GB 659 1432 23

Naas Branch Unit A3, M7 Business Park Naas, Co Kildare, Ireland Tel: 045 856 747 Freephone: 1800 30 1919 VAT # IE 6540968 P