

Product Specification



Product Title 4"GREASEPROOF BURGER DISCS 5000 PER PACK
Product Code BD45000

Description: Silcoat is a bleached, high density paper, manufactured from virgin fibre with high chemical purity, coated on both sides with silicone.

Usage: An environmental-friendly reusable baking paper offering excellent release properties, suitable for interleaving, baking, cooking up to 220°C and frying.

Property		Test Method	Unit	Typical Value
Grammage	Tolerance +/- 5%	ISO 536-1995 (E)	g/m ²	39
Bulking Thickness		ISO 534:2005 (E)	µm	55
Tensile Strength	MD	ISO 1974:1990 (E)	kN/m	3.3
Tear Resistance	CD	ISO 1974:1990 (E)	mN	200
Tear Resistance	MD	ISO 1974:1990 (E)	mN	170
Tear Resistance After heating 220oC	MD	ISO 1974:1990 (E)	mN	110
Wet Bursting Strength		ISO 2578	kPa	60
Water Absorptiveness	Cobb ⁶⁰ TS	ISO 535:1991 (E)	g/m ²	12

APPROVALS:

All raw materials and additives used in production comply with main food regulations. Certified according to ISO 9001 and BRC/IoP.

DECLARATION OF COMPLIANCE:

Based on analytical results from testing the paper grade mentioned above, this paper grade is judged to meet the requirements of the regulations referred to below for direct contact with dry, moist, and fatty foodstuffs.

EU Directive 1935/2004 *on Materials and articles intended to come into contact with food.*

Commission Regulation No. 2023/2006 *on G.M.P for materials and articles intended to come into contact with food.*

EU Directive 94/62/EC *on Packaging and Packaging Waste*

Foodstuffs, Consumer Goods, and Animal Feed Code – (22nd August 2011) *BGBI p 1770*

Recommendations BfR XXXVI and XXXVI/2 (State of September 2009)

FDA-CFR §176.170 – *Components of Paper and paperboard in contact with aqueous and fatty foods*

FDA-CFR §176.180 – *Components of Paper and paperboard in contact with dry food*

Recycling & Composting:

Silcoat paper is recyclable, if the local collection, sorting and appropriate infrastructure for recycling paper with silicone exists. Silcoat can also be composted and is certificated under DIN EN 13432:2000-12.

Customer Approval of Specification

Please sign and return this specification to technical@scobie-junor.co.uk to confirm formal acceptance of this specification. All specifications issued will be deemed to be accepted if no communication to the contrary is received after 10 working days.

Signature:

While we have taken all reasonable steps to verify the accuracy of the information contained in this specification, no warranties are given to this effect and purchasers should determine for themselves whether products are suitable for their own specific use. The information contained in this specification is intended for the customer it has been issued to. It must not be reproduced, or the information contained therein passed on to any third party without the written consent of Scobie & Junor.

Product Specification



Print name:	
Position:	
Date:	

Issued by Scobie & Junor (Estd. 1919) Ltd. Certified accurate on 18/08/2021 12:19:13

While we have taken all reasonable steps to verify the accuracy of the information contained in this specification, no warranties are given to this effect and purchasers should determine for themselves whether products are suitable for their own specific use. The information contained in this specification is intended for the customer it has been issued to. It must not be reproduced, or the information contained therein passed on to any third party without the written consent of Scobie & Junor.