

# Product Specification



Product Title GREASEPROOF BAKING SHEET 450MM X 750MM 480/PK  
Product Code BP450750

**Description:** Silcoat is a bleached, high density paper, manufactured from virgin fibre with high chemical purity, coated on both sides with silicone.

**Usage:** An environmental-friendly reusable baking paper offering excellent release properties, suitable for interleaving, baking, cooking up to 220°C and frying.

Property		Test Method	Unit	Typical Value
Grammage	Tolerance +/- 5%	ISO 536:1995 (E)	g/m <sup>2</sup>	39
Bulking Thickness		ISO 534:2005 (E)	µm	55
Tensile Strength	MD	ISO 1974:1990 (E)	kN/m	3.3
Tear Resistance	CD	ISO 1974:1990 (E)	mN	200
Tear Resistance	MD	ISO 1974:1990 (E)	mN	170
Tear Resistance After heating 220oC	MD	ISO 1974:1990 (E)	mN	110
Wet Bursting Strength		ISO 2578	kPa	60
Water Absorptiveness	Cobb <sup>60</sup> TS	ISO 535:1991 (E)	g/m <sup>2</sup>	12

## APPROVALS:

All raw materials and additives used in production comply with main food regulations. Certified according to ISO 9001 and BRC/loP.

## DECLARATION OF COMPLIANCE:

Based on analytical results from testing the paper grade mentioned above, this paper grade is judged to meet the requirements of the regulations referred to below for direct contact with dry, moist, and fatty foodstuffs.

EU Directive 1935/2004 on Materials and articles intended to come into contact with food.  
Commission Regulation No. 2023/2006 on G.M.P for materials and articles intended to come into contact with food.  
EU Directive 94/62/EC on Packaging and Packaging Waste  
Foodstuffs, Consumer Goods, and Animal Feed Code – (22nd August 2011) BGBl p 1770  
Recommendations BfR XXXVI and XXXVI/2 (State of September 2009)  
FDA-CFR §176.170 – Components of Paper and paperboard in contact with aqueous and fatty foods  
FDA-CFR §176.180 – Components of Paper and paperboard in contact with dry food

## Recycling & Composting:

Silcoat paper is recyclable, if the local collection, sorting and appropriate infrastructure for recycling paper with silicone exists. Silcoat can also be composted and is certificated under DIN EN 13432:2000-12.

## Customer Approval of Specification

Please sign and return this specification to [technical@scobie-junor.co.uk](mailto:technical@scobie-junor.co.uk) to confirm formal acceptance of this specification. All specifications issued will be deemed to be accepted if no communication to the contrary is received after 10 working days.

Signature:

Print name:

Position:

Date:

Issued by Scobie & Junor (Estd. 1919) Ltd. Certified accurate on 19/08/2021 13:24:39

While we have taken all reasonable steps to verify the accuracy of the information contained in this specification, no warranties are given to this effect and purchasers should determine for themselves whether products are suitable for their own specific use. The information contained in this specification is intended for the customer it has been issued to. It must not be reproduced, or the information contained therein passed on to any third party without the written consent of Scobie & Junor.