Product Specification



Product Title	4.5" SQUARE BURGER PAPERS 27000 PER BOX
Product Code	BP4527000

PRODUCT SPECIFICATION

57gsm Silcoat

<u>Description:</u> Silcoat is a bleached, high density paper, manufactured from virgin fibre with high chemical purity, coated on both sides with silicone.

<u>Usage:</u> An environmental-friendly reusable baking paper offering excellent release properties, suitable for interleaving, baking, cooking up to 220°C and frying.

Property		Test Method	Unit	Typical Value
Grammage	Tolerance +/- 5%	ISO 536	g/m ²	<i>57</i>
Bulking Thickness		ISO 534	μm	79
Tensile Strength	MD	ISO 1924-2	kN/m	5
Tear Resistance	CD	ISO 1974	mN	320
Tear Resistance	MD	ISO 1974	mN	300
Water Absorptiveness	Cobb ⁶⁰ TS	ISO 535	g/m²	14

APPROVALS:

All raw materials and additives used in production comply with main food regulations. Certified according to ISO 9001 and BRCGS.

DECLARATION OF COMPLIANCE:

Based on analytical results from testing the paper grade mentioned above, this paper grade is judged to meet the requirements of the regulations referred to below for direct contact with dry, moist, and fatty foodstuffs.

EU Directive 1935/2004 on Materials and articles intended to come into contact with food.

Commission Regulation No. 2023/2006 on G.M.P for materials and articles intended to come into contact with food.

EU Directive 94/62/EC on Packaging and Packaging Waste

Foodstuffs, Consumer Goods, and Animal Feed Code – (22nd August 2011) BGBI p 1770

Recommendations BfR XXXVI and XXXVI/2 (State of September 2009)

FDA-CFR §176.170 – Components of Paper and paperboard in contact with aqueous and fatty foods

FDA-CFR §176.180 — Components of Paper and paperboard in contact with dry food

Recycling & Composting:

Silcoat paper is recyclable, if the local collection, sorting and appropriate infrastructure for recycling paper with silicone exists. Silcoat can also be composted and is certificated under DIN EN 13432:2000-12.

While we have taken all reasonable steps to verify the accuracy of the information contained in this specification, no warranties are given to this effect and purchasers should determine for themselves whether products are suitable for their own specific use. The information contained in this specification is intended for the customer it has been issued to. It must not be reproduced, or the information contained therein passed on to any third party without the written consent of Scobie & Junor.

Product Specification



Customer Approval of Specification					
Please sign and return this specification to technical@scobie-junor.co.uk to confirm formal acceptance of this					
specification. All specifications issued will be deemed to be accepted if no communication to the contrary is					
received after 10 working days.					
Signature:					
Print name:					
Position:					
Date:					

Issued by Scobie & Junor (Estd. 1919) Ltd. Certified accurate on 06/12/2024 13:49:08

While we have taken all reasonable steps to verify the accuracy of the information contained in this specification, no warranties are given to this effect and purchasers should determine for themselves whether products are suitable for their own specific use. The information contained in this specification is intended for the customer it has been issued to. It must not be reproduced, or the information contained therein passed on to any third party without the written consent of Scobie & Junor.