

Product Specification



Product Title	VACUUM POUCH 200 X 300 RECYCLABLE 1000 PER BOX
Product Code	SC65R200300

MB - Medium barrier film

Product: VISHVACU, VISHBARR, VISHFORM, VISHTOP

Structure: PA/PE Multilayer Co-extruded barrier film

Excellent: Seal ability & Mechanical strength

Property	Method	Value
AVG. THICKNESS 2σ (+/- 10 %)		65
DART IMPACT (Gm. at 66 cm)	ASTM D1709-03	>400
TENSIL STRENGTH (N/15 mm)		
MD	ASTM D-882	>30
TD	ASTM D-882	>30
ELONGATION (%)		
MD	ASTM D-882	> 400
TD	ASTM D-882	> 400
C.O.F. (F→F)		
INNER	ASTM D-1894	<0.3
OTR 23 °C/ 0 % Rh (cc/m ² /day)	ASTM D3985-05	≤69
WVTR 38 °C & 90 % RH (gm/m ² /day)	ASTM F 1249-06	≤7

Storage recommendations: Store in a clean, cool & dry place 15-35°c, 30-80 %RH, for up to 12 months. Do not store in daylight or outside. Protect from rain & direct sunlight. Avoid direct contact to floor and walls. Keep in original packaging and remove all the protective packaging material before using the products.



Food Compliance: The films are made of raw materials (inputs) such as polymers used in the above products suitable for food contact in according to FDA and/or EC regulations.

All information given on this sheet has approximated value to the best of our knowledge and is for unformed film only. We do not hold out the parameters for damaged or stretched films. The user/customers are solely responsible for determining the suitability of the product in each case for their intended use. The parameters above are for reference purpose only and we disclaim any express or implied warranty or guarantee for the same. Vishakha assumes no liability or obligation that may arise from the use of this data. This sheet in full or in part, shall not be used to make any misleading claims or for any legal purposes.

While we have taken all reasonable steps to verify the accuracy of the information contained in this specification, no warranties are given to this effect and purchasers should determine for themselves whether products are suitable for their own specific use. The information contained in this specification is intended for the customer it has been issued to. It must not be reproduced, or the information contained therein passed on to any third party without the written consent of Scobie & Junor.

Product Specification



Customer Approval of Specification	
Please sign and return this specification to technical@scobie-junor.co.uk to confirm formal acceptance of this specification. All specifications issued will be deemed to be accepted if no communication to the contrary is received after 10 working days.	
Signature:	
Print name:	
Position:	
Date:	

Issued by Scobie & Junor (Estd. 1919) Ltd. Certified accurate on 16/05/2022 13:28:48

While we have taken all reasonable steps to verify the accuracy of the information contained in this specification, no warranties are given to this effect and purchasers should determine for themselves whether products are suitable for their own specific use. The information contained in this specification is intended for the customer it has been issued to. It must not be reproduced, or the information contained therein passed on to any third party without the written consent of Scobie & Junor.