

Product Specification Data Sheet



Code: F101214010

Product: as-223600-52

Std Description: SMOOTH WALL RECT. TRAY

Customer Description:

General Features

Body Style: SMOOTHWALL
Body Shape: RECTANGULAR
Flange Style: FLAT
Rim Style: REVERSE FULL CURL
Base Feature: STANDARD
Material: ALUMINIUM
Outside Lacquer: SIL
Inside Lacquer: SIL
Lidding Suitability: FILM SEAL
Scope of temperature: -40°C to 300°C
Use: The storage of strongly acidic or strongly salted foodstuffs in contact with uncoated aluminium should be avoided. A packaging test must always be carried out by the food manufacturer in order to determine the exact shelf life and functionality.

General Dimensions

Top Out (mm) ± 0.5 :	322.0 x 262.0
Top In (mm) ± 0.5 :	298.0 x 238.0
Base (mm) ± 0.5 :	282.0 x 222.0
Vertical Depth (mm) ± 0.5 :	60.0
Cubic Capacity (cm ³):	3,600
Gauge (mm) $\pm 8\%$:	0.130
Temper:	H22
Net Container Weight (gms) $\pm 8\%$:	48.89

Pack Features

Pack Quantity:	290
Poly Sleaving:	Yes
Carton Size (L x W x H):	593 x 398 x 353
Pack Volume (M ³):	0.083
Net Pack Weight (Kg):	14.18
Gross Pack Weight (Kg):	15.33

Pallet Features

Pallet Type: PALLET-EU
Pallet Edge Protection: Yes
Cartons per Layer: 4
Layers per Pallet: 6
Cartons per Pallet: 24
Containers per Pallet: 6,960
Pallet Dimensions (L x W x H): 1200 x 800 x 2268
Gross Pallet Volume (M³): 2.000
Gross Pallet Weight (kg): 388

Product manufactured in the United Kingdom
All products conform to Regulation (EC) No. 1935/2004 of the European Parliament and of the Council on materials and articles intended to come into contact with food

16 September 2021

Authorised:


Chief Executive Officer

Version No'



This specification is the property of i2r Packaging Solutions Limited and should not be copied or disclosed to anyone without the written consent of the Company