



## **FEELERS VINYL EXAM GLOVES SPECIFICATION**

### **POWDERED & POWDER FREE**

**CE SIMPLE DESIGN 06-07-16**

#### **Colours**

Natural and Blue

#### **Manufactured to**

ISO9001:2000  
ISO13485:2003  
ISO 14001 Environmental  
EC Directive 93/42/EEC  
EC Directive 2002/72/EC  
Intended for single use only  
EN455 1-3  
EN374-2 and 4  
EN420  
AQL 1.5  
EN1186 Suitable for food contact  
Powdered Gloves are GMO FREE (Cornstarch)  
These Gloves are **Recyclable** and **Latex Free**

#### **Physical Sizes (mm)**

	<b>S</b>	<b>M</b>	<b>L</b>	<b>XL</b>	<b>error (mm)</b>
Width of palm	85	95	105	115	+/-3
Thickness of finger tip	0.08	0.08	0.08	0.08	+/-0.02
Thickness of wrist	0.06	0.06	0.06	0.06	+/-0.02
Thickness of palm	0.08	0.08	0.08	0.08	+/-0.02
Length	245	245	245	245	+/-5
Wt per 1000 gloves	3.8kg	4.3kg	4.8kg	5.3kg	+/-0.2kg

#### **Physical Properties**

Tensile strength	Min. 10 MPa
Ultimate elongation	Min. 300%
Conditions of ageing:	70 +/- 2degC at 72 +/- 2 h

#### **Chemical Composition**

PVC, DINP, Ca-Zn stearate.

#### **Lubrication Powder Not Genetically Modified**

An absorbable dusting powder specially processed from cornstarch. It is highly resistant to swelling in hot water, steam and chemicals. This powder can be subjected to most sterilisation procedures without any effect on the unique characteristics of the powder.

**Packaging**

100 ambidextrous gloves per box.10 boxes per case

**OR**

100 ambidextrous gloves per Polypack 20 packs per case

Dimension of inner box approx. 210 x 110 x 60mm, 400gsm card and machine varnished. Wt. 52g each

Dimension of outer case (boxes) approx. L235 x H220 x W315mm, 150gsm with 125gsm corrugated single wall.

Wt. 230g each

Dimension of outer case (boxes) approx. L465 x H220 x W315mm, 150gsm with 125gsm corrugated twin wall.

Wt. 435g each

**PLEASE NOTE**

Our glove complies with the REACH Regulations that came into effect at 1<sup>st</sup> January 09 and that BAN'S the use of DOP in the manufacture of Vinyl gloves, it is replaced by DINP.