

Foil Reference

1391SPLHTP



top in (mm) 230 X 164	base (mm) 219 X 153		. ,	capacity (cc)
Specifications				
Туре	Chicken tray	Chicken tray		
Flange Style	Rolled Edge	Rolled Edge		
Base Style Ridged				
Material	Smoothwall	Smoothwall Foil Container Strip		
Gauge (micron)	180	180		
eight/1000 (kgs)	27.85 (+/-	27.85 (+/- 8% tolerance)		
Quantity per Case	230	230		
oer Layer / Pallet	11 Cases	11 Cases 44 Cases		
eight gross (kgs)	7.05	7.05		
limensions (mm)		355 x 270 x 380		
	Type Flange Style Base Style Material Gauge (micron) eight/1000 (kgs) Quantity per Case per Layer / Pallet eight gross (kgs) dimensions (mm)	Specifications Type Chicken trav Flange Style Rolled Edge Base Style Ridged Material Smoothwall Gauge (micron) 180 eight/1000 (kgs) 27.85 (+/- Quantity per Case 230 per Layer / Pallet 11 Cases eight gross (kgs) 7.05	Specifications Type Chicken tray Flange Style Rolled Edge Base Style Ridged Material Smoothwall Foil Conta Gauge (micron) 180 eight/1000 (kgs) 27.85 (+/- 8% tolerar Quantity per Case 230 per Layer / Pallet 11 Cases eight gross (kgs) 7.05 dimensions (mm) 355 x 270 x 380	Specifications Type Chicken tray Flange Style Rolled Edge Base Style Ridged Material Smoothwall Foil Container Strip Gauge (micron) 180 eight/1000 (kgs) 27.85 (+/- 8% tolerance) Quantity per Case 230 per Layer / Pallet 11 Cases 44 Ceight gross (kgs) 7.05 limensions (mm) 355 x 270 x 380

We confirm that the foil containers made by Coppice Alupack to the above specification are suitable for direct food contact. It is the customer's responsibility to ensure the suitability of the packaging medium chosen for the type of food to be packed therein through their own programme of shelf and/or other testing procedures.



Isfryn Industrial Estate Blackmill, Bridgend O/19 Mid Glamorgan, CF35 6EQ Tel 01656 840711 Fax 01656 841552 www.coppicealupack.com

www.coppicealupack.com sales@coppicealupack.co.uk

COPPICE

Coppice Alupack Ltd