

Technical Data Sheet

Product Name:

Bondpad - BPWAG18

Structure: EMBOSED



Hot perforated HDPE (White)



Airlaid with Spongel

Laminated product by hot melt technology

Characteristic	Unit	Method	Min	Mean *	Max
Grammage	gr/m2	M.I.P.1	94	105	116
Absorption in solution NaCl 0,2%	gr/m2	M.I.A.10	1620		
Thickness	mm	EN 29073		1,11	
Tensile strenght - Dry MD	N/50mm	ISO 9073 - 3		n.r.	
Tensile strenght - Dry CD	N/50mm	ISO 9073 - 3		n.r.	
Elongation at max. force - Dry MD	%	ISO 9073 - 3		n.r.	
Elongation at max. force - Dry CD	%	ISO 9073 - 3		n.r.	

* where not specified, tolerance +/- 10%

Law requirements

ABSORBING PAD SUITABLE FOR FOOD CONTACT REFERRING TO REG 1935/2004 AND 2023/2006

MAGIC CAN ASSURE THE PERFORMANCE OF THE PRODUCT UNTIL 12 MONTHS FROM THE DATE OF SHIPMENT IF:

- STORED IN A DRY AND FRESH ATMOSPHERE (HUMIDITY 40-70%) AT AMBIENT TEMPERATURE (5-30°C)
- STORED FAR FROM SOURCE OF HEAT AVOIDING DIRECT EXPOSURE IN THE LIGHT OF THE SUN

Date: 17/02/2021
Rev: 0

Issued by: *Alberto Scungo*
Quality Lab Manager Magic s.r.l.