

DS1200P7_s - HIGH SPEED DOUBLE STUFFER OUTPUT: UP TO 1200 UNITS PER HOUR - 2500 METERS PER DAY









DS1200P7_s - HIGH SPEED DOUBLE STUFFER OUTPUT: UP TO 1200 UNITS PER HOUR - 2500 METERS PER DAY



Pnuematics manufactured by Festo. Spare parts are easily accessable worldwide through Festo distributors or direct from SCOTNET.



Emergency Stop buttons mounted on both sides.

Breaked Castors, ensuring secure footing while working and easy





Injects a fine spray of water into each chamber each cycle to allow easy movement of dry products such as pork.

SSL Selectable Stroke Length

Allows shortening of piston strokes, to optimise shape.

APH Automatic Piston Hold

Pausing the piston in its outward position, to allow further shaping of the product.

Available in all sizes from 75 - 200 mm EH version available for tube sizes up to 250 mm



Ewon - Operating on either LAN or sim card - our remote access to the machine allowing your engineers or ours diagnose faults remotely.



Operated with compressed air and single phase power supply.

movement when required.



The entire DS1200P range is controlled by PILZ safety relays. All connnetions are at least IP65 or above, ensuring reliability in even the wettest environments.



HMI controlling machine functions, reporting output and efficiency figures, password protection and engineering diagnostics.



Chamber sides open for easy cleaning and fast tool-less size change.









